


Dual-Pol Antenna CMA-B/6521/E0-6



X-Pol: 1710-2180

Electrical specification:

Frequency range per input (MHz)	2 x 1710-2180		
Frequency band definitions (MHz)	1710-1880	1850-1990	1920-2180
Polarization	Dual linear $\pm 45^\circ$		
Gain (dBi)	20.3	20.7	21.2
Horizontal = 3 dB beamwidth ($^\circ$) $\pm 3^\circ$	65	63	61
Vertical = 3 dB beamwidth ($^\circ$) $\pm 0.3^\circ$	4.4	4.2	3.9
Adjustable electrical downtilt ($^\circ$)	0 - 6		
Front to back ratio, $\pm 30^\circ$ total power (dB)	> 25		
First upper sidelobe suppression (dB)	0 $^\circ$, 3 $^\circ$, 6 $^\circ$ >18, >17, >17		
First nullfill below horizon (dB)	< 20		
Cross-polar discrimination +/-0 $^\circ$ (dB)	> 20		
Cross-polar discrimination +/-60 $^\circ$ (dB)	> 10		
VSWR	< 1.5:1		
Isolation between inputs (dB)	> 30		
Sector power ratio	5 %		
Antenna efficiency*	94 %		
Inter modulation, IM3 (dBc)	<-153 @2x43 dBm, typical <-160		
Nominal impedance	50 Ω		
Max power per input	500 W		

Mechanical specification:

Connectors	2 x 7/16 female
Connector position	Bottom
Lightning protection	DC grounded
Height/Width/Depth mm (in)	2060 (81.1) / 196 (7.7) / 122 (4.8)
Antenna weight	16 kg (35 lb)

Wind load at 42 m/s (94 mph) :

Frontal:	360 N (81 lbf)
Lateral:	154 N (35 lbf)
Rear:	266 N (60 lbf)
Survival wind speed	67 m/s (150 mph)
Colour radome	Light Grey, RAL 7035
Radome material	ASA

Mounting hardware:

Mounting bracket	2
Bracket weight (complete)	5.2 kg (11.5 lb)
Pole diameter	45-120 mm (1.8-4.7 in)
Tilt bracket	0 $^\circ$ - 5 $^\circ$ mechanical

Ordering information:

CMA-B/6521/E0-6/MET	110040 B
CMA-B/6521/E0-6/RET	110050 B